

■ Model: GYM12S5-1P

Powered by YANMAR (JAPAN BRAND)



■ Generator Specification

Service	PRP ⁽¹⁾	ESP ⁽²⁾
Power (KVA)	10	11
Power (KW)	10	11
Rated speed	1500RPM	
Standard voltage	220, 230, 240V	
Power factor	1.0	
Phase	Single	

Performance Data		
Model	GYM12S5-1P	
Engine brand	YANMAR	
Engine model	3TNV88	
Speed control type	Mechanical	
Alternator brand	LEROY SOMER	
Alternator model	TAL-A40-C	
Control system	SMARTGEN HGM420N	
Starter motor voltage	12V	
Frequency	50Hz	
Fuel Consumption (L/H)	100% Prime Load	/
	75% Prime Load	/
	50% Prime Load	/
	25% Prime Load	/



GENLITEC Power gensets are compliant with ISO 9001 and CE standard, which include the following directives:

- 2006/42/EC Machinery safety.
- 2006/95/EC Low voltage
- EN 60204-1: 2006+A1: 2009, EN ISO 12100: 2010, EN ISO 13849-1:2008, EN 12601: 2010

• GYM12S5-1P: SILENT TYPE

(1) PRP (Prime Power)

According to ISO 8528-1, prime power is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during at 24 hours period shall not exceed 80% of the prime power. 10% overload available for governing purposes only.

(2) ESP (Standby Power)


According to ISO 8528-1. It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 hours of operation per year (of which no more than 300 hours for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufactures. No overload capability is available.

Voltage (V)	ESP		PRP		Current Amps
	KVA	KW	KVA	KW	
240	11	11	10	10	41.7
230	11	11	10	10	43.5
220	11	11	10	10	45.5

Standard Reference Conditions

Note: Standard reference condition 25°C (77°F) air inlet temp. 100m (328ft) A.S.L 30% relative humidity. Fuel consumption date with diesel fuel with specific gravity of 0.85 and conforming to BS 2869: 1998 Class A2

Dimension & Weight



Dimension	Open type	Silent type
Length (L)	1450mm	2000mm
Width (W)	720mm	850mm
Height (H)	900mm	1150mm
Net Weight	520kg	680kg

Note: This parameters allows for some acceptable deviations.



■ Engine Specification



MODEL: YANMAR 3TNV88

Cylinder number	3
Aspiration system	Natural
Cooling method	Water cooled
Combustion system	Direct injection
Bore x Stroke (mm)	88x90
Compression ratio	19:1
Rated speed (RPM)	1500
Displacement (L)	1.642
Rated power (KW)	12.2
Standby power (KW)	13.2
Fuel injection pump	YPD-MP2
Firing order	1-3-2-1
Oil capacity (L)	6.7
Coolant capacity (L)	2
Starter motor capacity	DC 12V – 1.2A

■ Alternator Specification



MODEL: LEROY SOMER TAL-A40-C

Number of phase	Single
Rated power (KW/KVA)	10/10
Frequency (Hz)	50
Power factor (Cos Phi)	1.0
Poles	2
Temp. rise	125K
Insulation type	H class
Ambient temp.	40°C
IP rating	IP23
Excitation system	Self-excited
Bearing	Single bearing
Coating	Vacuum impregnation
Voltage regulator	A.V.R
Coupling	Flexible disc

Standard Supply Scope

- Industrial exhaust silencer
- Maintenance free battery
- Water cooling radiator
- A.V.R
- Flexible pipes
- Battery wires
- Wiring diagram
- Build-in based fuel tank
- Float Battery charger
- Manual books
- Tool kits
- Emergency stop button
- Base frame
- Digital control panel
- Main circuit breaker

■ Optional Supply Scope

Engine	Alternator	Generator Sets	Control Panel
<ul style="list-style-type: none"> ○ Water jacket pre-heater ○ Lubrication oil pre-heater ○ Battery isolator 	<ul style="list-style-type: none"> ○ Anti-condensation heater ○ PMG ○ STAMFORD alternator 	<ul style="list-style-type: none"> ○ Extended fuel tank 12h/24h/72h ○ Soundproof canopy ○ Trailer mounted 	<ul style="list-style-type: none"> ○ Remote control system ○ Build-in/External ATS ○ Power output sockets



Control Panel

Configuration

- Emergency stop button
- Protection MCB (Main circuit breaker)
- Float battery charger
- ATS connection
- AMF digital control module
- Fuel level meter
- Controller power switch
- Alarm buzzer

Features

- Chinese, English, Spanish, Turkish, Russian & French language
- Three phase generator monitoring
- Automatic or manual start/stop of the gensets
- Push buttons for simple control & operation
- Generator measurements (50Hz/60Hz)
- Precision collect & display parameters about ENGINE
- Comprehensive shutdown or warning on fault condition
- Three phase generator protections
 - Over / under voltage
 - Over / under frequency
 - Current / voltage asymmetry
 - Over current / overload
- Three phase AMF function
 - Over / under voltage
 - Loss of phase detection function
- Emergency start function
- IP55 waterproof with rubber-ring gasket



Control Module Model: SMARTGEN HGM420N

Display	LCD (132 x 64)
Operation panel	Silicon rubber
Digital input	4
Relay output	6
Analogue input	4
AMF	Yes
AC System	1P2W / 2P3W / 3P3W / 3P4W
Alternator voltage	15-360V (ph-N)
Alternator frequency	50/60Hz
KW/Amp Detecting & Display	Yes
Monitor interface	USB
Programmable interface	USB
DC supply	DC 8-35V
Operating temp.	-25 ~ +70°C

Controller Module Options

SMARTGEN	COMAP	DEEPSEA
HGM6110/HGM6120N	AMF25	DSE6020

FORTE POWERTECH PTY LTD

1/47 Ellemsea Circuit, Lonsdale, SA 5160, AUSTRALIA

All information in the document is substantially correct at the time of printing
But may be subsequently altered by the company.

